

Nokia Wavence

Ultra-Broadband Transceiver Millimeterwave 80 | (ETSI/ANSI)


The Nokia Wavence Ultra-Broadband Transceivers (UBT) provide high-capacity, low latency microwave transport for shorthaul and small cells backhaul applications. The UBT-m 80 is a compact radio unit operating in the E-Band. Using the most advanced radio technologies and multi-frequency carrier aggregation, the UBTs support backhaul and Ethernet fronthaul evolutions with multi-gigabit capacities and low latency transport with best in class system gain.

The UBT-m 80 is integrated in the Nokia Network Services Platform for common management and fully compatible with the Nokia Microwave Service Switches (MSS) and the rest of the Nokia microwave portfolio.

Two options are proposed : UBT-m with Standard Power and UBT-mX with eXtended power for longer links.

UBT-m 80	
Application	<ul style="list-style-type: none"> • Macro cell backhaul (access and hub) • Split-mount or standalone configuration • Small cell backhaul
Physical	240mm x 220mm x 80 mm (9.4 in. x 8.7 in. x 3.1 in.)
Interfaces	<ul style="list-style-type: none"> • 1 x DC port • Three GE ports: (1 x 100/1000 Base T RJ45 PFoE and 2 x 1/2.5/10 Gbit Optical SFP) • 1 x XPIC port • 100x1000 Base T RJ45 used as default management port or as user port
Radio	<ul style="list-style-type: none"> • 71-76/81-86 GHz (FDD) • 10 Gb/s standard • 20Gb/s in XPIC • Channels: 62.5 MHz to 2GHz
Modulation	<ul style="list-style-type: none"> • BPSK to 512QAM • Support for Adaptive Baud Rate

Weight	• 3.8kg
Power	<ul style="list-style-type: none"> • -48 V (-30V to -57V) • PFoE • UBT-m: 50 W • UBT-mX: 53 W



UBT-m 80 standalone

Technical specifications

UBT-m 80

Indoor/outdoor connections

- Maximum electrical cable length 100 m (328 ft) with Cat5e cable
- Longer distance with optical fiber (depends on fiber type)

Radio

- 1+0, 2+0, 1+1 HSB
- Carrier aggregation
- XPIC support
- Typical Tx power: UBT-m 16dBm
UBT-mX : 20dBm
- Support for adaptive coding and modulation (ACM) and adaptive baud rate (ABR)
- Latency one way down to 10 usec
- Duplex technology: FDD
- Timing transport: IEEE 1588v2-PTP, SyncE
- ITU-T G.8264 support

Networking

- Ethernet interface: One electrical 100/1000Base-T, two (1G/2.5G/10G) optical SFP+ plug-ins
- Advanced QoS: Support for IEEE 802.1p, Diffserv, TTL and strict priority
- Dynamic scheduling according to air interface changes
- VLAN: IEEE 802.1P, IEEE 802.1Q, Q-in-Q support
- ERPS: ITU-T G.8032
- Ethernet OAM (IEEE 802.1ag, ITU-T Y.1731, IEEE 802.3ah)
- L3 VPN support
- SDN support
- Netconf/Yang support

Environmental

- Operating temperature: -40°C up to +55°C (-40°F up to +131°F)

- ETSI Class 4.1 (EN 300019-1-4), ANSI GR 3108 Class 4, GR-950, GR-63
- IP 67

Standards compliance

Regulatory

- Radio Equipment Directive 2014/53/EU - RED
- EN 302 217, FCC Part101, ISED Canada

Safety

- EN 60950-1, EN 60825-1, 60825-2, GR-1089, GR-3108

EMC

- EN 301 489-1, EN 301 489-4, GR-1089, IEEE1613

Metro Ethernet Forum

- MEF 2.0, MEF 8, MEF 9, MEF 14, MEF 22

Services

- Architecture and design
- Network planning
- Equipment and site engineering
- Installation services
- Integration services
- Performance analysis, network assessment, DCN, synchronization and QoS assessment
- Maintenance 24x7 technical support
- Return for repair or advanced exchange

Management:

- Secure FTP for software download and backup
- IPv4/IPv6 management
- Embedded web browser for network element configuration and monitoring
- Intuitive supervision systems
- SNMP agent with TCP/IP rerouting capability
- Nokia NSP Network Services platform



Disclaimer: Nokia operates a policy of ongoing development and has made all reasonable efforts to ensure that the content of this document is adequate and free of material errors and omissions. Nokia assumes no responsibility for any inaccuracies in this document and reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

About Nokia

We create the technology to connect the world. Powered by the research and innovation of Nokia Bell Labs, we serve communications service providers, governments, large enterprises and consumers, with the industry's most complete, end-to-end portfolio of products, services and licensing.

From the enabling infrastructure for 5G and the Internet of Things, to emerging applications in digital health, we are shaping the future of technology to transform the human experience. networks.nokia.com

Nokia is a registered trademark of Nokia Corporation. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.

© 2020 Nokia

Nokia Oyj
Karaportti 3
FI-02610 Espoo, Finland
Tel. +358 (0) 10 44 88 000

Document code: SR1805025960EN (Feb) CID 210156